TECHNICAL DATA SHEET

ORIANT RACER SYNTHETIC SAE 10W-40 API SN

DESCRIPTION:

ORIANT Racer SAE 10W-40 API SN is a synthetic technology engine oil developed for the most recent requirement of gasoline passenger engines. It meets all current industry standard requirements of domestic car makers recommending API SM.

APPLICATION:

ORIANT RAER SYNTHETIC can be used under the most difficult operating conditions (highways, congested city traffic, etc.) for every season. Recommended for all petrol engines (multi-valve and turbo types) turbo-charged or naturally aspirated in cars.

BENEFITS:

- Longer oil life and lower oil consumption.
- Outstanding protection against wear, rust, corrosion, and exceptional engine cleanliness.
- Exceptional thermal stability and oxidation resistance.
- Reduce engine maintenance
- Outstanding low temperature fluidity.

SPECIFICATION:

API - SN
ILSAC GF-5
ACEA A3/B4

Meets Performance:
TOYOTA, KIA, NISSAN, SUZUKI, HONDA & HYUNDAI

Sr. No	Test Parameters *SAE Viscosity Grade*	Test Method	Typical *SAE 10W-40*
1	Appearance	Visual	C&B
2	Density @ 15°C gm/cm^3	ASTM D1298	0.855
3	Viscosity Index	ASTM D2270	152
4	Viscosity @ 100°C (cSt)	ASTM D 445	15.92
5	Pour Point °C	ASTM D 97	-36
6	Flash Point (COC) °C	ASTM D 92	234
7	T.B.N mg KOH/gm	ASTM D 2896	7.5

The above figures are typical of those obtained with normal production tolerance and do not constitute specifications